Hawkeye Industries™

SLOW THE SET, NOT THE JOB

the best way to add working time & increase productivity

GELTIME EXTENDER (39GELX-01)

ADDITIVE

DURATEC™

SURFACING TECHNOLOGY





GEL TIME EXTENSION

Increase the catalyzed pot life by at least 100%, with minimal extension of cure time.

COMPATIBLE CHEMISTRY

Designed to work along with the Duratec polyester and vinyl ester chemistry.

INCREASED PRODUCTIVITY

Increasing the pot life means more Duratec can be catalyzed and the risk of setting up in the spray gun is reduced.

BEAT THE HEAT

Longer pot life makes it easier to use Duratec products on a hot day.

ABOUT THE PRODUCT

Duratec Gel Time Extender (39GELX-01) is a specialty additive engineered to double the pot life of Duratec polyester and vinyl ester coatings without significantly affecting cure time. Whether you're working in high temperatures or spraying large areas, Gel-X gives you the time and control to coat efficiently without setting up in the gun or rushing the job.

ABOUT THE MARKET

Used across marine, aerospace, and composite tooling environments, Gel Time Extender is ideal for shops battling high temps or large projects. It's a simple solution to a common production problem: not enough time in the pot. With increased open time, fabricators gain better coverage with fewer restarts, especially during hot weather.

HOW TO USE

Thoroughly mix the Duratec product you intend to use. Measure out the amount that will be applied in 20-25 minutes. Add 2% Duratec Gel-X to the product and mix thoroughly. Catalyze product according to instructions. If thinner is necessary, we recommend Duratec 39UCE. Spray according to directions.

Note: *This product is 100% volatile. If the container is left open, the material will evaporate, and the strength and performance of material will be compromised. This product is formulated to work with Duratec polyester and vinyl ester products. Compatibility with any other polyester or vinyl ester coatings is not assured and must be tested by the customer for suitability.*

+1 909-546-1160 help@hawkeyeind.com www.hawkeyeind.com